

Artikel Nr.	Eingang		Ausgang	Einschaltdauer	Schutzart	Gewicht	Vergleichbar Honeywell Nr.		
	V~	Hz*	A*	V	mA*	%	kg		
F51041782	230	50 (60)	0,5	5000	15	20	IP 20	0,9	TZI 5-15/20W
F51041767	230	50 (60)	0,45	5000	15	100	IP 20	1,5	TZI 5-15/100W
F51041543	230	50 (60)	1,1	7000	25	20	IP 20	1,5	TZI 7-25/20W
F51042765	230	50 (60)	0,6	7500	12	100	IP 20	2	TZI 7,5-12/100W
F51042695	230	50 (60)	0,9	7500	20	33	IP 20	2	TZI 7,5-20/33W
F51041768	115	50 (60)	1	5000	15	20	IP 20	0,9	TZI 5-15/20R
F51041766	115	50 (60)	0,9	5000	15	100	IP 20	1,5	TZI 5-15/100R
F51041768	115	50 (60)	2,2	7000	25	20	IP 20	1,5	TZI 7-25/20R
F51042764	115	50 (60)	1,2	7500	12	100	IP 20	2	TZI 7,5-12/100R
F51042745	115	50 (60)	1,8	7500	20	33	IP 20	2	TZI 7,5-20/33R

F51842767	230	50 (60)	0,45	5000	15	100	IP 65	3	TGI 5-15/100W
F51842783	230	50 (60)	1,1	7000	25	20	IP 65	3	TGI 7-25/20W
F51842784	230	50 (60)	0,6	7500	12	100	IP 65	3,5	TGI 7,5-12/100W
F51842367	230	50 (60)	0,9	7500	20	33	IP 65	3,5	TGI 7,5-20/33W
F51842790	115	50 (60)	0,9	5000	15	100	IP 65	3	TGI 5-15/100R
F51842791	115	50 (60)	2,2	7000	25	20	IP 65	3	TGI 7-25/20R
F51842764	115	50 (60)	1,2	7500	12	100	IP 65	3,5	TGI 7,5-12/100R
F51842745	115	50 (60)	1,8	7500	20	33	IP 65	3,5	TGI 7,5-20/33R